

TECHNO ACOUSTIC PIPE AND FITTING

SOUNDPROOF DRAINAGE SYSTEM

Product Description :

Techno Acoustic pipes and fittings are specialized components used in various applications to manage and control sound within piping systems. The components are designed to reduce noise, vibrations, and acoustic disturbances that can occur in piping systems due to fluid flow or mechanical operations. Techno Acoustic piping system is a superior soundproofing waste system that provides unsurpassed noise reduction and construction benefits.

APPLICATION :

Tested and approved for soil and waste discharge for application area code "B" in accordance with EN 1451-1; with diameters ≥ 50 mm permitted also for underground discharge systems up to the main sewer junction.



TEMPERATURE RESISTANCE :

Short-term exposure: max. 95 °C

Long-term exposure: max. 98 °C

Minimum Installation Temperature :

Impact resistance tested to EN 1451 at -10 °C

Pipe Dimensions :

50 , 75 , 110 , 160 , 200



TECHNO

Main Features :

-  Excellent Acoustic Performance
-  Wide Range of Diameters
-  High UV Resistance
-  Excellent Resistance to High Temperature
-  Stable Assembly
-  Smoother and Increased Flow
-  High Impact Resistance
-  High Chemical Resistance
-  10Years Warranty

Certificates :



Internal Layer

Grey PP provides the best flow performance and high-definition contrast for visual inspection.

Middle Layer

PP and PP-MD provide high mechanical resistance and excellent soundproofing performance.

External Layer

Black PP provides excellent impact resistance and long-term UV protection.



TECHNO ACOUSTIC



WWW.TECHNOPIPE.COM

TECHNO ACOUSTIC PIPE AND FITTING

SOUNDPROOF DRAINAGE SYSTEM

Product Description :

Techno Acoustic pipes and fittings are specialized components used in various applications to manage and control sound within piping systems. The components are designed to reduce noise, vibrations, and acoustic disturbances that can occur in piping systems due to fluid flow or mechanical operations. Techno Acoustic piping system is a superior soundproofing waste system that provides unsurpassed noise reduction and construction benefits.

APPLICATION :

Tested and approved for soil and waste discharge for application area code "BD" in accordance with EN 1451-1; with diameters ≥ 50 mm permitted also for underground discharge systems up to the main sewer junction.



TEMPERATURE RESISTANCE :

Short-term exposure: max. 95 °C

Long-term exposure: max. 98 °C

Minimum Installation Temperature :

Impact resistance tested to EN 1451 at -10 °C

Pipe Dimensions :

50 , 75 , 110 , 160 , 200



Main Features :

-  Excellent Acoustic Performance
-  Wide Range of Diameters
-  Smoother and Increased Flow
-  Excellent Resistance to High Temperature
-  Stable Assembly
-  10Years Warranty
-  High Impact Resistance
-  High Chemical Resistance

Certificates :



Internal Layer

Grey PP provides the best flow performance and high-definition contrast for visual inspection.

Middle Layer

PP and PP-MD provide high mechanical resistance and excellent soundproofing performance.

External Layer

Grey PP provides excellent impact resistance and long-term UV protection.



TECHNO

TECHNO ACOUSTIC



WWW.TECHNOPIPE.COM